

ZULJANA'S INDUSTRIAL TOUCHSCREEN PCS ZL215PC-C

INDUSTRIAL TOUCH PCS & RUGGED COMPUTERS SOLUTIONS

Zuljana industrial Computers are made to perform in severe production settings at the highest capacity possible. Made with miraculous resilience and performance, our industrial touch pcs computers can be found in numerous form factors, screen sizes, and configurations.


BaoBao can custom industrial pc for almost any application and worksite problem. We offer the current CPUs and internal hardware to ensure our clients receive best-in-class efficiency and a solution.



Industrial Touch PC Features

- Intel[®] Core I3-3217U
- 64GB Zuljana Industrial SSD
- 4GB DDR3 RAM
- Supports Win7/8/10, Linux (32Bit, 64Bit)
- Extensive industrial and consumer interfaces
- 10-Finger-Multi Touch Capacitive Touch Panel
- Patented IP65 front
- Audio amplifier with speakers
- 1 years guarantee





www.baobao-industries.com

Ordering information

21.5" Touch Panel PC with Intel® Core I3-3217U and Ubuntu 18.04 Embedded

IP Rating

IP65 Front / IP40 Back

LCD Panel

Screen Diagonal (Inch/cm) Active Display Area(cm) Aspect Ratio Physical Resolution Maximum showable resolution Colours Displayed Brightness (cd/m2) Contrast Typical Reaction Time Tr/ Tf (ms) Visual Angle Horizontal / vertical (°) Backlight/Backlight Lifetime (hours)

Touch Panel

Touch Technology Touch Panel Drivers Touch Life (Contacts) Surface Hardness Surface Treatment 47.76(H)×26.91(V2) 16:9 1920×1080 1920×1080 16.7M 500 1000:1 1.5/3.5 170/160 LED/40,000

21.5/54.69

Projected Capacitive 10-point Multitouch Windows; Linux; Mac; Android Unlimited 7H Anti-glare (Optional)

External Connectors

1 x 12V DC-In (screwable);1x W-LAN antenna connector (RP-SMA male);2 x USB 3.0;2x USB 2.0;1 x HDMI;1 x MIC-In & EAR-Out;1x BT Antenna Connector;1 x DP;3 x COM port Full-PIN - RS232/485; 5V/12V;2 x 10/100/1000Mbit RJ45 Ports

Product Name Model Number

PC System

CPU Chipset Graphic/GPU Audio

Memory Storage Network Driver Support Pre Installed

Operation/Mechanical

Operating Temperature (°C) Humidity Range (RH) Net Weight(Kg) Gross Weight(Kg) Housing Material Housing(mm)L x W x H Mounting

Power

Power Indicator Power Supply

Working Power (V) Working Power (w) Stand-By Consumption 21.5 Inch Industrial Panel PC ZL215PC-C

Intel® Core I3-3217U Intel® NM70 express chipset Intel® Graphics 4000 Realtek ALC662 6 channel high fidelity audio chip 4GB DDR3L non-ECC Zuljana Industrial 64GB SSD 2 x Realtek PCIe GB LAN 8111G; W-LAN Win7/8/10; Linux; 32Bit/64Bit Linux Ubuntu

-10 ~ +60 10% − 90% 6.7 7.9⊠incl.cartonage2 Aluminum Case 523.0 × 314.7 × 51.8 VESA 100

Green LED 100-240V ACDC active switching; 12V DC-Out 12 24 <1

