

# ZULJANA'S

## SLOT MACHINE TOUCH SCREEN MONITOR

# ZLF24LTM



### HIGHLIGHTS:

- 23.8" TFT-LCD with LED Backlight
- Resolution: 1920 × 1080
- Brightness: 250 Nits
- VGA, DVI, DP, USB (Type B)
- Multicolor LED RGB Lights
- Spill and Dust Resistant
- Complete FAN Free Design
- Aluminum Cabinet
- Completely Refined Design



## Slot Machine Touch Screen Monitors

BaoBao Industrial is the leading manufacturer and supplier of slot machine touch screen monitors that feature elegant designs and industrial-grade specifications for high performance. Our touch screen monitors are specifically designed for Casinos and Gaming that operate 24/7 continuously even in high temperatures and challenging environments.

With 400 Nits high brightness and 10 Points Capacitive touch screens, our LED light bar touch screen monitors provide a smooth and exciting gaming experience. Available in 24", 27", 32", and 43" sizes with HD, FHD, and 4K resolution.

## Technical Specifications

### ZLF24LTM

Product Details		Power Supply	
Product Name:	23.8 Inch Slot Machine Touch Monitor	Monitor:	+12VDC ± 5%
Model Number:	ZLF24LTM	RGB LED Lights:	+5VDC ± 5%
<b>LCD Panel</b>		Optional LED controller (external):	+12VDC ± 5%
Display Technology	Active Matrix TFT-LCD with LED Backlight	Power Consumption (Max.)	36W ( Monitor without RGB LED Lights) 30W (RGB LED Lights)
Aspect Ratio	16:9	<b>Operation / Mechanical</b>	
Active Area (W × H)	527.04 × 296.46mm	Case/Bezel Color	Dark grey
Native resolution	1920 × 1080	Mounting Options	VESA: 100 × 100 mm, 75 × 75mm
Response Time (Typ.)	14ms	Outline Dimensions (W×H×D)	591.00mm × 367.00mm× 49.80mm
Display Colors	16.7M	On-Screen Display (OSD)	Control (back): Power, Auto, Up, Down, Menu
Brightness (cd/m <sup>2</sup> )	250nits	Operating Altitude	≤3000m
Contrast	1000:1	Temperature Range	Operating: 0°C to 40°C Storage: -20°C to 60°C
Typical reaction time div/ Tf (ms)	14ms	Humidity Range (RH)	Operating: 20% to 80% Storage: 10% to 90%
Visual Angle horizontal/vertical (°)	Horizontal (left/right) CR≥10 89°/89° Vertical (up/down) CR≥10 89°/89°	I/O	VGA, DVI, DP, USB (Type B)
Backlight/Backlight Lifetime(hours)	LED/50,000	Carton Box Dimensions (L x W x H)	690mm × 260mm × 460mm
<b>Touch Panel</b>		Net weight (Kg)	8
Touch Technology	Projected Capacitive (PCAP)	Gross weight (Kg)	20
Surface Treatment	Anti-glare (Optional)	LED Lights Color	Multicolor
Thickness	4.3±0.3mm	LED Lights Location	Front: 2 LED lights bar Back: 3 LED lights bar
Light Transmission	≥83%	Agency Approvals	CE, FCC
Response Time (Typ.)	8ms	System Support	Win7 or later, Linux 4.4 or later
Touch Screen Interface	USB	LED Controller (external)	Optional
Touch Point	10	Warranty	1 year

### I/O Connectors

